

Maxcompact Screw Compressor

The Maxcompact is a rotary screw compressor mounted on a tank that is completely preassembled and tested on the assembly line.

Water proof control panel with star-delta motor starting, complete with all functional and operational safety devices.

The new MSA series, a silenced and oil injected rotary screw compressor.

Compressed air receiver with pressure stabilization function and condensate separator. The receiver rests on a structure that allows for easy handling.

Installation is extremely simple; just position the machine, connect the air output to the air distribution network and make the electrical connection.



Type	bar	HP	kW	cfm	dB(A)	L	W	H	Air Receiver Litres
MSA 5,5/8 + V340	8	7,5	5,5	27,9	64	1450	650	1685	340
MSA 5,5/10 + V340	10	7,5	5,5	22,3	64	1450	650	1685	340
MSA 7,5/8 + V340	8	10	7,5	39,6	64	1450	650	1685	340
MSA 7,5/10 + V340	10	10	7,5	35,3	64	1450	650	1685	340
MSA 7,5/13 + V340	13	10	7,5	27,9	64	1450	650	1685	340
MSA 11/8 + V340	8	15	11	57,2	63	1450	650	1685	340
MSA 11/10 + V340	10	15	11	49,5	63	1450	650	1685	340
MSA 11/13 + V340	13	15	11	42,8	63	1450	650	1685	340
MSA 15/8 + V340	8	20	15	70,7	65	1450	650	1685	340
MSA 15/10 + V340	10	20	15	63,3	65	1450	650	1685	340
MSA 15/13 + V340	13	20	15	51,9	65	1450	650	1685	340
MSA 5,5/8 + V500	8	7,5	5,5	27,9	64	1750	670	1750	500
MSA 5,5/10 + V500	10	7,5	5,5	22,3	64	1750	670	1750	500
MSA 7,5/8 + V500	8	10	7,5	39,6	64	1750	670	1750	500
MSA 7,5/10 + V500	10	10	7,5	35,3	64	1750	670	1750	500
MSA 7,5/13 + V500	13	10	7,5	27,9	64	1750	670	1750	500
MSA 11/8 + V500	8	15	11	57,2	63	1750	670	1750	500
MSA 11/10 + V500	10	15	11	49,5	63	1750	670	1750	500
MSA 11/13 + V500	13	15	11	42,8	63	1750	670	1750	500
MSA 15/8 + V500	8	20	15	70,7	65	1750	670	1750	500
MSA 15/10 + V500	10	20	15	63,3	65	1750	670	1750	500
MSA 15/13 + V500	13	20	15	51,9	65	1750	670	1750	500