

Mini Screw Compressor

Version with base



Especially suitable for installations near which compressed air is needed or as an extension to existing installations. The electric compressor chiefly comprises: suction filter, compressor, electric motor, oil filter and cooler, air-cooling system, start-up and regulation control panel, support base and stylish, anti-noise housing.

Version on tank

Especially suitable for new or independent installations where compressed air with a low noise level is needed. The unit consists of a compressor and tank.



Dry Version



Especially suitable for installations that need to produce compressed air with a low dew-point. The unit consists of a compressor, a tank and a refrigerating dryer using R 134 gas: it features a dew-point indicator and timed condensate discharge. When oil-free compressed air is required, the unit can be fitted with a series of de-oiling filters.

Floor Mounted Version

Type	bar	HP	kW	cfm	dB(A)	Volt/Hz/Ph	Air Receiver Litres	L	W	H
MSM 2,2 B	10	3	2,2	8,5	61	230/50/1	-	620	605	950
MSM 2,2 B	10	3	2,2	8,5	61	400/50/3	-	620	605	950
MSM3 B	10	4	3	11,3	61	400/50/3	-	620	605	950
MSM4 B	10	5,5	4	16,6	62	400/50/3	-	620	605	950
MSM4 BX	10	5,5	4	16,6	62	400/50/3	-	620	605	950
MSM 5,5 BX	10	7,5	5,5	21,2	64	400/50/3	-	620	605	950

Tank Version

Type	bar	HP	kW	cfm	dB(A)	Volt/Hz/Ph	Air Receiver Litres	L	W	H
MSM 2,2	10	3	2,2	8,5	61	230/50/1	200	1420	575	1255
MSM 2,2	10	3	2,2	8,5	61	400/50/3	200	1420	575	1255
MSM 3	10	4	3	11,3	61	400/50/3	200	1420	575	1255
MSM 4	10	5,5	4	16,6	62	400/50/3	200	1420	575	1255
MSM 4 X	10	5,5	4	16,6	62	400/50/3	200	1420	575	1255
MSM 5,5X	10	7,5	5,5	21,2	64	400/50/3	200	1420	575	1255

Dry Version (compressor - dryer)

Type	bar	HP	kW	cfm	dB(A)	Volt/Hz/Ph	Air Receiver Litres	L	W	H
MSM 2,2D	10	3	2,2	8,5	61	230/50/1	200	1420	575	1255
MSM 2,2D	10	3	2,2	8,5	61	400/50/3	200	1420	575	1255
MSM 3 D	10	4	3	11,3	61	400/50/3	200	1420	575	1255
MSM 4 D	10	5,5	4	16,6	62	400/50/3	200	1420	575	1255
MSM 4 DX	10	5,5	4	16,6	62	400/50/3	200	1420	575	1255
MSM 5,5 DX	10	7,5	5,5	21,2	64	400/50/3	200	1420	575	1255